

型式Model		BJW SERIES系列貫流式熱水鍋爐			
		BJW-15	BJW-20	BJW-30	BJW-40
發熱量Capacity	Kcal/Hr	150,000	200,000	300,000	400,000
傳熱面積 Heating Surface	M ²	6.6	6.6	8	9.7
最高使用壓力M. A. W. P	kg/cm ²	10			
產熱水量 (15-60°C)	加侖/小時G. P. H.	800	1,100	1,600	2,200
Water Value	公升/小時L. P. H.	3,300	4,400	6,600	8,800
重油HEAVY OIL	L/Hr	-	-	35.5	47.3
柴油DIESEL OIL	L/Hr	20.3	27.0	40.5	54.1
天然瓦斯LNG	NM ³ /Hr	18.5	24.7	37.1	49.4
液化瓦斯LPG	Kg/Hr	13.8	18.3	27.5	36.7
燃燒控制 Control Method Of Combustion		全自動控制Fully Automatic Control			
		ON-OFF			ON-OFF & Hi-Low-OFF
溫度控制 Control Method Of Temperature		全自動可調式溫度控制 Automatic Adjustable Temp. Control			
安全裝置 Safety Device		火焰檢出器、燃燒保護器、溫度控制器、爐水超溫保護及壓力安全閥			
		Flame Detector, Burning Protector, Temperature Controller, Water overheat protection and Pressure Safety Valve			
給水管 Water Inlet	φ mm	40/50	40/50	50/65	50/65
熱水管 Hot Water Outlet	φ mm	40/50	40/50	50/65	50/65
回水管Hot Water Return	φ mm	40/50	40/50	50/65	50/65
排水管 Drain	φ mm	25	25	25	25
柴油入口Diesel Inlet	φ mm	15	15	15	15
重油入口Heavy Oil Inlet	φ mm	-	-	40	40
LNG入口LNG Inlet	φ mm	25	25	40	40
LPG入口LPG Inlet	φ mm	25	25	40	40
鍋爐全長 Boiler Length	L mm	1300	1300	1470	1470
鍋爐全寬 Boiler Width	W mm	900	900	1000	1000
鍋爐全高 Boiler Hight	H mm	1850	1850	2150	2250
煙囪口徑 Chimney Dia.	φ mm	200	200	250	250
製品重量Weight of Products	kg	650	650	980	1100
循環幫浦 Hot Water Cir. Pump	視加熱之溫度差所計算出之循環水量而定。 (溫水泳池、空調取暖、工業製程等) Heating Circulation:To be decided by the circulation rate that is calculated from the heating temperature difference. (Swimming pool heating, Air-conditioning heating, Industrial process heating, etc.)				

*本表所列規格及尺寸因裝備改良等原因恕不另行通知。

**本規格以外之型式可另行設計製造；另有(柴油/瓦斯)雙燃料及沼氣機種。