

| 型式Model | | BJW SERIES系列貫流式熱水鍋爐 | | | |
|------------------------------------|---|--|---------|---------|---------|
| | | BJW-50 | BJW-60 | BJW-70 | BJW-80 |
| 發熱量Capacity | Kcal/Hr | 500,000 | 600,000 | 700,000 | 800,000 |
| 傳熱面積 Heating Surface | M ² | 9.9 | 9.9 | 9.9 | 9.9 |
| 最高使用壓力M. A. W. P | kg/cm ² | 10 | | | |
| 產熱水量 (15-60°C) | 加侖/小時G. P. H. | 2,700 | 3,300 | 3,800 | 4,400 |
| Water Value | 公升/小時L. P. H. | 11,100 | 13,300 | 15,500 | 17,700 |
| 重油HEAVY OIL | L/Hr | 59.1 | 71.0 | 82.8 | 94.6 |
| 柴油DIESEL OIL | L/Hr | 67.6 | 81.1 | 94.6 | 108.1 |
| 天然瓦斯LNG | NM ³ /Hr | 61.8 | 74.2 | 86.5 | 98.9 |
| 液化瓦斯LPG | Kg/Hr | 45.8 | 55.0 | 64.2 | 73.3 |
| 燃燒控制 Control Method Of Combustion | | 全自動控制Fully Automatic Control | | | |
| | | Hi-Low-OFF | | | |
| 溫度控制 Control Method Of Temperature | | 全自動可調式溫度控制 Automatic Adjustable Temp. Control | | | |
| 安全裝置 Safety Device | | 火焰檢出器、燃燒保護器、溫度控制器、爐水超溫保護及壓力安全閥 | | | |
| | | Flame Detector, Burning Protector, Temperature Controller, Water overheat protection and Pressure Safety Valve | | | |
| 給水管 Water Inlet | φ mm | 65/80 | 65/80 | 80 | 80 |
| 熱水管 Hot Water Outlet | φ mm | 65/80 | 65/80 | 80 | 80 |
| 回水管 Hot Water Return | φ mm | 65/80 | 65/80 | 80 | 80 |
| 排水管 Drain | φ mm | 25 | 25 | 25 | 25 |
| 柴油入口 Diesel Inlet | φ mm | 15 | 15 | 15 | 15 |
| 重油入口 Heavy Oil Inlet | φ mm | 40 | 40 | 40 | 40 |
| LNG入口 LNG Inlet | φ mm | 50 | 50 | 50 | 50 |
| LPG入口 LPG Inlet | φ mm | 50 | 50 | 50 | 50 |
| 鍋爐全長 Boiler Length | L mm | 1750 | 1750 | 1750 | 1750 |
| 鍋爐全寬 Boiler Width | W mm | 1500 | 1500 | 1500 | 1500 |
| 鍋爐全高 Boiler Hight | H mm | 2500 | 2500 | 2600 | 2600 |
| 煙囪口徑 Chimney Dia. | φ mm | 300 | 300 | 300 | 300 |
| 製品重量 Weight of Products | kg | 1400 | 1400 | 1500 | 1500 |
| 循環幫浦 Hot Water Cir. Pump | 視加熱之溫度差所計算出之循環水量而定。 (溫水泳池、空調取暖、工業製程等) Heating Circulation: To be decided by the circulation rate that is calculated from the heating temperature difference. (Swimming pool heation, Air-conditioning heating, Industrial process heating, etc.) | | | | |

*本表所列規格及尺寸因裝備改良等原因恕不另行通知。

**本規格以外之型式可另行設計製造；另有(柴油/瓦斯)雙燃料及沼氣機種。